Ubuntu SHP CI-4 15W-40

Heavy-duty multigrade engine oil

UB-TDS-004 | Revision 0.1 | 16 October 2026

Applications

Four-stroke diesel fleet engines and specified petrol engine applications.

Performance features

Wear control; engine cleanliness; resistance to foaming.

Reference performance specifications

API CI-4/SL ACEA E7(E5)/A3/B3/B4 GLOBAL DHD-1 JASO DH-1 MB 228.3 / MB 229.1 Volvo VDS-3 MAN M 3275; Renault Trucks RLD/RLD-2 MTU/DDC Type 2 Cummins CES 20071/72/76/77/78 MACK EO-M Plus Caterpillar ECF-1 Allison C-4 Deutz DQC-III-05

Reference designations require verification for the Ubuntu formulation. Ubuntu certification, licensing and OEM approval have not been established.

Reference typical characteristics

SAE Viscosity Grade	Unit	15W-40
Kinematic Viscosity @ 40C	cSt	100
Kinematic Viscosity @ 100C	cSt	14.5
Viscosity Index		150
Pour Point	C	-27
Flash Point (PMCC)	C	207
TBN	mgKOH/gm	11.4
Sulphated Ash	% mass	1.5
Density @ 20C	kg/l	0.885

DRAFT: Technical values have not been verified for the Ubuntu formulation. Confirm product identity, batch data, specifications and the applicable safety data sheet before release or use. Typical values are not manufacturing limits.