Ubuntu Agri Super 15W-40

Super tractor oil universal (STOU)

UB-TDS-025 | Revision 0.1 | 16 October 2026

Applications

Specified tractor engines, transmissions, hydraulics, wet brakes and power steering systems.

Performance features

Wet-brake friction control; load carrying; thermal stability.

Reference performance specifications

API CG-4/SF ACEA E3 API GL-4 Mack EO-K /2 Caterpillar TO-2 John Deere20C/J27 Ford M2C 34D,159B/C; New Holland 82009201/2/3 Massey Ferguson CMS M 1135, 1139, 1143,1144 and 1145 Sperry Vickers/Eaton 1-280-S GM Allison C-4 ZF TE ML 06A, B (also includes ZF TE ML 06R), C and 07B

Reference designations require verification for the Ubuntu formulation. Ubuntu certification, licensing and OEM approval have not been established.

Reference typical characteristics

SAE Viscosity Grade	Unit	15W-40
Kinematic Viscosity @ 40C	cSt	106
Kinematic Viscosity @ 100C	cSt	14
Viscosity Index		133
Pour Point	C	-30
Flash Point (PMCC)	C	220
TBN	mgKOH/gm	11.0
Sulphated Ash	% mass	1.38
Density @ 20C	kg/l	0.886

DRAFT: Technical values have not been verified for the Ubuntu formulation. Confirm product identity, batch data, specifications and the applicable safety data sheet before release or use. Typical values are not manufacturing limits.