Ubuntu Grease MF EP 00 / 2 / 3

Multi-purpose lithium EP grease range

UB-TDS-042 | Revision 0.1 | 16 October 2026

Applications

Specified bearings, chassis points and automotive or industrial grease systems. Select consistency to match the lubrication system.

Performance features

Load carrying; pumpability; water resistance.

Reference performance specifications

No formal performance specification was published for this family.

Reference designations require verification for the Ubuntu formulation. Ubuntu certification, licensing and OEM approval have not been established.

Reference typical characteristics

NLGI Consistency	00	2	3
Thickener	Lithium	Lithium	Lithium
Colour	Light brown	Light brown	Light brown
Structure	Smooth	Smooth	Smooth
Worked Penetration @ 25°C .1mm (ASTM D217)	415	280	235
Dropping Point °C (ASTM D2265)	170	180	190
Timken OK Load kg (ASTM D2509)	25	25	25
Base Oil KV mm²/s at 40°C (ASTM D445)	200	200	200

Application notes

Reference table includes NLGI 3 in addition to the 00 and 2 grades named in the menu. All three are retained pending range confirmation. Reference operating range: -30 to 120 C.

DRAFT: Technical values have not been verified for the Ubuntu formulation. Confirm product identity, batch data, specifications and the applicable safety data sheet before release or use. Typical values are not manufacturing limits.